



| Di Neck | Thread Spec. |
|---------|--------------|
| φ42 | PZ27.8 |
| | W28.8x1/14 |
| | 25T |
| | 25E |
| | 1x14BS |
| φ48 | 3/4-14NGT |
| | W28-14 |
| | 1-11.5NGT |

Technical requirements

Application standard: ISO 9809-1:2019 & EN ISO 9809-1:2019

Filling contents: compressed gases or liquified gases as per ISO 11114-1

Environmental temperature: -50°C to 65°C

Material: 37Mn

| Chemical Composition % | C | Mn | Si | S | P | S+P | V+Nb+Ti+B+Zr+Sn | Cr | Ni | Mo | Cu |
|------------------------|-----------|-----------|-----------|--------|--------|--------|-----------------|-------|-------|-------|-------|
| | 0.34-0.38 | 1.40-1.70 | 0.10-0.35 | ≤0.010 | ≤0.020 | ≤0.025 | ≤0.15 | ≤0.20 | ≤0.20 | ≤0.15 | ≤0.20 |

Hydraulic test pressure: 250bar

Working pressure: 150bar

Technical data

| Specification | Water capacity (L) | 50 | 58 | 60 | 67 | 67.5 | 68 | 70 | 75 | 80 | 82 | |
|---------------|--------------------|--------------------------|------|------|------|------|------|------|------|------|------|------|
| | | Length ±20(mm) | 1120 | 1280 | 1320 | 1460 | 1470 | 1480 | 1520 | 1615 | 1715 | 1755 |
| | | Empty weight approx (kg) | 54.9 | 62.0 | 63.7 | 69.8 | 70.2 | 70.7 | 72.4 | 76.6 | 81.0 | 82.7 |

仅供销售参考

Digitally signed by Sherry Song
 DN: cn=Sherry Song, o=AIS,
 ou=US, UK, PT, CN,
 email=sherry.song@arrowheadis.c
 om, c=CN
 Reason: I have reviewed this
 document
 Date: 2021.12.20 19:17:44 +08'00'

| Rev0.0 | | | | GAS CYLINDER | ISO267-Mn-00 | | |
|--------|---------|------|------------|--------------|--|--------|-------|
| | | | | | QUANTITY | WEIGHT | SCALE |
| NO. | INDEX | SIGN | DATE | 37Mn | | | |
| DESN | Wen xj | REVD | | | | | |
| DRAN | | APPD | Shao gx | | | | |
| CHKD | Chen yf | | | TOTAL 1 PAGE | Shandong Yongan Special Equipment Co., Ltd | | |
| | | DATE | 2021.10.20 | | | | |