

Type Examination Certificate

This is to certify that:

FirePro Systems Ltd
8 Faleas Str.
Agios Athanasios Industrial Area
Limassol
CY-4101
Cyprus

Holds Certificate Number:

BSI/MED/3.46/755612

In respect of:

MED/3.46

Equivalent Fixed Gas Fire Extinguishing Systems Components for Machinery Spaces (Aerosol Systems)

MED/3.46 - Equivalent fixed gas fire extinguishing systems for machinery spaces (aerosol systems).

Product Description - Aerosol Fire Extinguishing Units with dry condensed extinguishing agent, Fire Class A & B Models - FP20S, FP20SE, FP40S, FP80S, FP100S, FP-100EX, FP200S, FP-200EX, FP500S, FP-500EX, FP1200, FP1200S, FP-1200EX, FP2000, FP2000S, FP-2000EX, FP3000, FP3000S, FP-3000EX, FP4200T/TS, FP-4200EX, FP5700, FP5700S & FP-5700EX.

Specified standard: IMO MSC/Circ 1270 incl Corr.1 as amended.

On the basis that BSI carried out the relevant EU type examination procedures for the equipment identified above which was found to be in compliance with the Marine Equipment Directive (MED) 2014/90/EU as amended, subject to any conditions in the schedule attached hereto. The attached schedule of approval forms part of this certificate.

For and on behalf of BSI, a Notified Body for the above Directive (Notified Body Number 2797):

Denelise L'Ecluse, Managing Director Assurance - Continental Europe

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Product Specification

The products listed below are to be installed with an actuation system/panel where manual activation is achieved as defined in MSC1/Circ 1270 chapter 17 and as per the relevant FirePro User/Installation manual. The actuation system/panel is excluded from this certification.

FP20S:	Aerosol generating fire extinguishing system unit with 20g dry condensed extinguishing agent, Fire Class A & B
FP20SE:	Aerosol generating fire extinguishing system unit with 20g dry condensed extinguishing agent, Fire Class A & B
FP40S:	Aerosol generating fire extinguishing system unit with 40g dry condensed extinguishing agent, Fire Class A & B
FP80S:	Aerosol generating fire extinguishing system unit with 80g dry condensed extinguishing agent, Fire Class A & B
FP100S/FP-100EX:	Aerosol generating fire extinguishing system unit with 100g dry condensed extinguishing agent, Fire Class A & B
FP200S/FP-200EX:	Aerosol generating fire extinguishing system unit with 200g dry condensed extinguishing agent, Fire Class A & B
FP500S/FP-500EX:	Aerosol generating fire extinguishing system unit with 500g dry condensed extinguishing agent, Fire Class A & B
FP1200/FP1200S/FP-1200EX:	Aerosol generating fire extinguishing system unit with 1200g dry condensed extinguishing agent, Fire Class A & B
FP2000/FP2000S/FP-2000EX:	Aerosol generating fire extinguishing system unit with 2000g dry condensed extinguishing agent, Fire Class A & B
FP3000/FP3000S/FP-3000EX:	Aerosol generating fire extinguishing system unit with 3000g dry condensed extinguishing agent, Fire Class A & B
FP4200T/TS/FP-4200EX:	Aerosol generating fire extinguishing system unit with 4200g dry condensed extinguishing agent, Fire Class A & B
FP5700/FP5700S/FP-5700EX:	Aerosol generating fire extinguishing system unit with 5700g dry condensed extinguishing agent, Fire Class A & B

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 2 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Approval Documentation that forms part of this certification:

Drawing No.	Rev/Issue	Date	Title
C20EASS	1	27/05/2014	FP20SE – General Assembly Drawing
C40ASS	1	27/05/2014	FP40S – General Assembly Drawing
C80ASS	1	27/05/2014	FP80S – General Assembly Drawing
C1AS	4	27/05/2014	FP100S – General Assembly Drawing
C2AS	4	27/05/2014	FP200S – General Assembly Drawing
C5AS	4	27/05/2014	FP500S – General Assembly Drawing
B12AS	0	05/01/2016	FP1200 – General Assembly Drawing
B12EH	0	01/01/2008	FP1200 – External Housing Construction Drawing
B12IH	0	05/01/2016	FP1200 – Internal Housing Construction Drawing
B12IAS	0	05/01/2016	FP1200 – Internal Assembly Drawing
B20AS	0	05/01/2016	FP2000 – General Assembly Drawing
B20IAS	0	05/01/2016	FP2000 – Internal Assembly Drawing
B30AS	0	05/01/2016	FP3000 – General Assembly Drawing
B30IAS	0	05/01/2016	FP3000 – Internal Assembly Drawing
B2030EH	1	01/01/2008	FP2000 & FP3000 – External Housing Construction Drawing
B2030IH	0	05/01/2016	FP2000 & FP3000 – Internal Housing Construction Drawing
B122030BRKT	1	01/08/2012	FP1200/FP2000/FP3000 – Mounting Bracket
B42TAS	0	01/01/2008	FP4200 – General Assembly Drawing
B42TIAS	0	27/04/2014	FP4200 – Internal Assembly Drawing
BS57TEH	0	01/01/2008	FP4200 (FP5700T) – External Housing Construction Drawing
B57TIH	0	02/10/2014	FP4200 – Internal Housing Construction Drawing
B57AS	0	05/01/2016	FP5700 – General Assembly Drawing
B57EH	1	01/10/2008	FP5700 – External Housing Construction Drawing
B57IH	0	05/01/2016	FP5700 – Internal Housing Construction Drawing
B57IAS	0	05/01/2016	FP5700 – Internal Assembly Drawing
B57BRKT	2	02/10/2014	FP4200, FP5700 – Mounting Bracket
AELACT	0	01/01/2008	Electrical Activators for all Models.
B122030BRKT	1	01/08/2012	FP1200S, FP2000S, FP3000S – Mild Steel Mounting Bracket
B12EHBC	1	01/08/2012	FP1200S – External Housing Bottom Cover
B12EHSW	1	01/08/2012	FP1200S – External Housing Side Walls
B12EHTC	1	01/08/2012	FP1200S – External Housing Top Cover

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 3 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Approval Documentation that forms part of this certification (continued):

Drawing No.	Rev/Issue	Date	Title
B203057EHBC	1	02/10/2014	FP2000S, FP3000S, FP5700S – External Housing Bottom Cover
B203057EHTC	1	01/08/2012	FP2000S, FP3000S, FP5700S – External Housing Top Cover
B2030EHSW	2	01/08/2012	FP2000S, FP3000S – External Housing Side Walls
B57BRKT	2	02/10/2014	FP5700S – Mounting Bracket
B57EHSW	2	01/08/2012	FP5700S – External Housing Side Wall
FP1EX	0	23/08/2018	FP-100EX - General Assembly Drawing
FP2EX	0	23/08/2018	FP-200EX - General Assembly Drawing
FP5EX	0	23/08/2018	FP-500EX - General Assembly Drawing
ATBR122030	0	23/08/2018	FP-1200EX, FP-2000EX, FP-3000EX – ATEX Mounting Bracket
ATBR57	0	23/08/2018	FP-4200EX, FP-5700EX – ATEX Mounting Bracket
FP1200EX	0	23/08/2018	FP-1200EX – ATEX Casing Assembly
FP2030EX	0	23/08/2018	FP-2000EX, FP-3000EX – ATEX Casing Assembly
FP4257EX	0	23/08/2018	FP-4200EX, FP-5700 – ATEX Casing Assembly
Supporting Documentation			
Technical Dossier	BSI Reference 7498123, 8030440, 8198682, 8636065, 3307535, 3498912 & 3855527. Latest Revision No.18 dated March 2023.		
Manuals	Information, Instruction & User Manual, EU Manual, Latest Version No.8, May 2020. Annex 1 Marine Manual Latest Revision No.5 Aug 2021. Design Installation & Maintenance Manual for ATEX Applications Version 1, rev. 0, 2/11/2018.		

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 4 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Approval Documentation that forms part of this certification (continued):

Reports & Certificates	KIWA Certificate K21477/08 01/04/2010 UL Test Report, Project Ref 05CA05359, File EX6960 USCG Report CG-D-03-06 Russian Maritime Register of Shipping, Type approval Certificate Ref 10.80012.180 dated 11/06/2010 for MCS 1270 * Hughes Associates INC Analysis Report dated Nov 2004 & 15/01/2009 ** Cone Calorimeter Tests of IMO MSC Circ 1270 Class A Plastic Materials – Hughes Associates Inc (26/01/2021) Efectis Test Report R1134, Fire test - Wood Cribs & Plastic Sheets (Jan 2012) KIWA, EMC Test Report 126076-EMC (11/01/2013) KIWA Certificate K21774/14 UK (19/14/2014) – FPC Compound. KIWA Certificate K21774/17 UK (23/12/2016) – update to include FP 20T/40T/80T & FP 4200T models
-----------------------------------	---

* *The Russian Maritime Register of Shipping has made an independent evaluation of the test reports owned by FirePro and according to their opinion it satisfied the requirements of the MSC.1/Circ.1270. Since the Certification list is reporting all the approval documents received so far by FirePro, the Russian Registry Type Approval was included in the above list.*

** *The Hughes Report is that at the time MCA requested FirePro to run additional tests, the opinion of FirePro was that they had already run the additional tests as part of the listing with various accredited Institutes, such as UL. Therefore FirePro asked Hughes Associates, the largest in the world Fire Risk Assessment Company, to carry out an evaluation and provide their independent opinion on this issue. Mr.L.Borghetti (Hughes Europe) was the chairman of the CEN,ISO and IMO technical committees on the aerosol technology and therefore he is in position to give a competent opinion on the issue.*

The conclusion of Hughes Analysis Report is: " FirePro was participating and contributing to the research and test campaign headed by USCG, having the scope to develop the information necessary for the revision of the existing IMO MSC/Circ.1007 (now IMO MSC/Circ.1270). The FirePro Aerosol Extinguishing Systems passed all the tests and requirements stated by the revised IMO MSC/Circ.1270 as reported by the USCG, the polymeric Sheet Test has been witnessed as passed by the listing issued by the Underwriters Laboratories.

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 5 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Design Calculation:

Agent

The quantity (mass) of aerosol agent to be used should be determined as follows:

$$W = \frac{V \times q \text{ (g)}}{f}$$

where

W = Agent mass (g) (Total mass required to protect the specific volume)

V = Volume of enclosure (m³) (Protected volume)

q = Design application density (gr/m³) (net mass of agent per unit volume (g/m³) required by the system designer for the fire protection application)

f = Efficiency coefficient of generator's model (%) (net mass of agent delivered by a generator model (size))

q = 120 gr/m³

Efficiency coefficients (related to each generator model (size)):

FP-20S/SE= 60%

FP-1200/S = 63%

FP-40S= 61%

FP-2000/S = 60%

FP-80S= 59%

FP-3000/S = 61%

FP-100S = 61%

FP4200T/TS = 60%

FP-200S = 59%

FP-5700/S= 59%

FP-500S = 66%

The total number of generators (N) to be used is derived by the following formula

$$N = \frac{W \text{ (total agent mass)}}{\text{nominal mass (initial mass of the solid compound) of each generator model (size)}}$$

Example: FP2000 = 2000 grams of nominal mass

FP5700 = 5700 grams of nominal mass

Note: If different generator models (size) should be selected, the total mass of extinguishant (solid compound) shall not be less than the quantity required (W).

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 6 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Technical Specification

Model	FP-20S / FP20SE
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element with 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	310 g
Weight net extinguishing agent	20 g
Operational discharge time	5 - 10 seconds
Discharge outlet	2
Discharge length	0.6 m
Size	165 mm x 32 mm (incl. connector housing)
Self activation temperature	300 C

Model	FP-40S
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element with 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	610 g
Weight net extinguishing agent	40 g
Operational discharge time	5 - 10 seconds
Discharge outlets	2
Discharge length	1.2 m
Size	140 mm x 51 mm
Self activation temperature	300 C

See Product Specification note on Page 2

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 7 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Technical Specification

Model	FP-80S
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element with 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	870 g
Weight net extinguishing agent	80 g
Operational discharge time	5 - 10 seconds
Discharge outlets	2
Discharge length	2 m
Size	185 mm x 51 mm (incl. connector housing)
Self activation temperature	300 C

Model	FP-100S
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	Heating element with 2.3 ohm resistance
Current intensity to be tested	Maximum 5 mA
Weight gross	1370 g
Weight net extinguishing agent	100 g
Operational discharge time	5 - 10 seconds
Nozzle	optional
Discharge outlet	1
Discharge length	1 m
Size	155 mm x 84 mm (incl. connector housing)
Self activation temperature	300 C

See Product Specification note on Page 2

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 8 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Technical Specification

Model	FP-200S
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element with 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	1840 g
Weight net extinguishing agent	200 g
Operational discharge time	5 - 10 seconds
Nozzle	Optional
Discharge outlet	1
Discharge length	2 m
Size	185 mm x 84 mm (incl. connector housing)
Self activation temperature	300 C

Model	FP-500S
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element with 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	3340 g
Weight net extinguishing agent	500 g
Operational discharge time	5 - 10 seconds
Discharge outlet	1
Discharge length	2.5 m
Size	295 mm x 84 mm (incl. connector housing)
Self activation temperature	300 C

See Product Specification note on Page 2

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 9 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Technical Specification

Model	FP-1200 / FP1200S
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	10900 g (excl bracket)
Weight net extinguishing agent	1200 g
Operational discharge time	10 -15 seconds
Discharge outlet	1
Discharge length	3.5 m
Size	216 mm x 300 mm x 167 mm
Self activation temperature	300 C

Model	FP-2000 / FP2000S
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	15500 g
Weight net extinguishing agent	2000 g
Operational discharge time	10 - 15 seconds
Discharge outlet	1
Discharge length	3.5 m
Size	300 mm x 300 mm x 185 mm
Self activation temperature	300 C

See Product Specification note on Page 2

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 10 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Technical Specification

Model	FP-3000 / FP3000S
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	16300 g
Weight net extinguishing agent	3000 g
Operational discharge time	15 - 20 seconds
Discharge outlet	1
Discharge length	4 m
Size	300 mm x 300 mm x 185 mm
Self activation temperature	300 C

Model	FP-4200T/TS
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	23600 g
Weight net extinguishing agent	4200 g
Operational discharge time	15 - 20 seconds
Discharge outlet	1
Discharge length	5 m
Size	300 mm x 300 mm x 300 mm
Self activation temperature	300 C

Model	FP-5700 / FP5700S
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	26400 g
Weight net extinguishing agent	5700 g
Operational discharge time	15 - 20 seconds
Discharge outlet	1
Discharge length	8 m
Size	300 mm x 300 mm x 300 mm
Self activation temperature	300 C

See Product Specification note on Page 2

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 11 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Technical Specification

Model	FP-100EX
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	Heating element with 2.3 ohm resistance
Current intensity to be tested	Maximum 5 mA
Weight gross	1830 g
Weight net extinguishing agent	100 g
Operational discharge time	5 - 10 seconds
Nozzle	optional
Discharge outlet	1
Discharge length	1 m
Size	170 mm x 84 mm (incl. connector housing)
Self activation temperature	300 C

Model	FP-200EX
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element with 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	2315 g
Weight net extinguishing agent	200 g
Operational discharge time	5 - 10 seconds
Nozzle	Optional
Discharge outlet	1
Discharge length	2 m
Size	200 mm x 84 mm (incl. connector housing)
Self activation temperature	300 C

See Product Specification note on Page 2

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 12 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Technical Specification

Model	FP-500EX
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element with 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	3770 g
Weight net extinguishing agent	500 g
Operational discharge time	5 - 10 seconds
Discharge outlet	1
Discharge length	2.5 m
Size	310 mm x 84 mm (incl. connector housing)
Self activation temperature	300 C

Model	FP-1200EX
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	17050 g
Weight net extinguishing agent	1200 g
Operational discharge time	10 -15 seconds
Discharge outlet	1
Discharge length	3.5 m
Size	365 mm x 450 mm x 310 mm
Self activation temperature	300 C

See Product Specification note on Page 2

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 13 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Technical Specification

Model	FP-2000EX
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	21650 g
Weight net extinguishing agent	2000 g
Operational discharge time	10 - 15 seconds
Discharge outlet	1
Discharge length	3.5 m
Size	365 mm x 450 mm x 310 mm
Self activation temperature	300 C

Model	FP-3000EX
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	22450 g
Weight net extinguishing agent	3000 g
Operational discharge time	15 - 20 seconds
Discharge outlet	1
Discharge length	4 m
Size	365 mm x 450 mm x 310 mm
Self activation temperature	300 C

See Product Specification note on Page 2

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 14 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Technical Specification

Model	FP-4200EX
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	30910 g
Weight net extinguishing agent	4200 g
Operational discharge time	15 - 20 seconds
Discharge outlet	1
Discharge length	5 m
Size	365 mm x 450 mm x 420 mm
Self activation temperature	300 C

Model	FP-5700EX
Type	Cold
Activation mechanism	electrical (min 1.5 VDC, min 0.8 A in 3 - 4 sec)
Activator type	heating element 2.3 ohm resistance
Current intensity to be tested	maximum 5 mA
Weight gross	33710 g
Weight net extinguishing agent	5700 g
Operational discharge time	15 - 20 seconds
Discharge outlet	1
Discharge length	8 m
Size	365 mm x 450 mm x 420 mm
Self activation temperature	300 C

See Product Specification note on Page 2

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 15 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).

BSI Group The Netherlands B.V., registered in the Netherlands under number 33264284, at John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands
A member of BSI Group of Companies.

Type Examination Certificate

No. BSI/MED/3.46/755612

Schedule of Approval

Certificate Amendment Record and BSI internal Review relating to this Certificate

Issue date	Comments	BSI Review No.
October 2021	First Issue	2797:21:3499222
January 2023	5-year Re-certification	2797:22:3794673
March 2023	Updated to include Model FP-100EX, FP-200EX, FP-500EX, FP-1200EX, FP-2000EX, FP-3000EX, FP-4200EX & FP-5700EX.	2797:23:3855528

Conditions of Certification

- i) This certificate remains valid unless cancelled or revoked, provided the conditions listed below are complied with and the equipment remains satisfactory in service.
- ii) The equipment detailed on page 1 on this certificate is to be manufactured in accordance with Conformity to Type Based on Quality Assurance of the Production Process (Module D) of the Marine Equipment Directive.
- iii) The certificate will not be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with the approved body named on this certificate.
- iv) Should the specified regulations or standards be amended during the validity of this certificate, the products are to be re-approved prior to them being placed on board vessels to which the amended regulations or standards apply.
- v) Detailed User instructions are to be provided with each product.
- vi) The Aerosol units shall be used with an activation system complying with all the requirements of MSC.1/Circ.1270, in particular clauses 12.1, 14 and 17.
- vii) SOLAS 74 Reg. II-2/10, SOLAS 74 Reg. X/3, IMO Res.MSC.98(73)-(FSS Code) 5, IMO Res.MSC.36(63)-(1994 HSC Code) 7, IMO Res.MSC.97(73)-(2000 HSC Code) 7, IMO Res. MSC.391(95)-(IGF Code) 11, IMO MSC/Circ.1270 incl. Corr.1, IMO MSC.1/Circ.1313 requirements, as applicable.
- viii) Production tests are to be conducted in accordance with the applicable requirements of the IMO Resolutions and applicable standards and be recorded by the manufacturer in accordance with the approved Conformity to Type Based on Quality Assurance of the Production Process (Module D) of the Marine Equipment Directive.
- ix) Each item, batch or lot of the equipment is to have the "Mark of Conformity" affixed and be issued with a "Declaration of Conformity".

First Issued: 2021-10-29

Latest Issue: 2023-03-30

Expiry Date: 2027-11-14

Page: 16 of 16

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.
To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated [online](#).