



## Declaration

We hereby declare that the foam used in our FLAMETECH-brand foam fire extinguishers, specifically Firefilm3% AFFF, is procured from Shanghai Waysmos fire suppression Co., Ltd., and it is free from PFOS and PFOA.

The specific fire extinguisher models are as follows:

Model No	Description
FT01-06A-00/CE1	6litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:15bar,Fire rating 13A & 144B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/756478
FT01-06E-00	6litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:15bar,Fire rating 13A & 144B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/756478
FT01-09A-00/CE1	9litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:15bar,Fire rating 21A & 233B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/756478
FT01-09E-00	9litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:15bar,Fire rating 21A & 233B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/756478
FT01-02A-00/CE1	2litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:12bar,Fire rating 5A & 34B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/787404
FT01-02H-00	2litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:12bar,Fire rating 5A & 34B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/787404
FT01-03A-00/CE1	3litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:12bar,Fire rating 8A & 55B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/787404
FT01-03H-00	3litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:12bar,Fire rating 8A & 55B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/787404
FT01-06D-00/CE1	6litre AFFF foam,cartridge operated.Temperature range:5 °C to 60 °C working pressure:15bar,Fire rating 13A & 144B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/756478
FT01-09D-00/CE1	9litre AFFF foam,cartridge operated.Temperature range:5 °C to 60 °C working pressure:15bar,Fire rating 21A & 183B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/756478
FT01-06A(MOD4)-00/CE1	6litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:15bar,Fire rating 13A & 144B, Kitemark certificate No: KM709286,MED

# KXFIRE

	certificate No: BSI/MED/3.2/756478
FT01-09A(MOD4)-00/CE1	9litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:15bar,Fire rating 21A & 233B, Kitemark certificate No: KM709286,MED certificate No: BSI/MED/3.2/756478
FT03-047D-00	50litre AFFF foam,stored pressure.Temperature range:5 °C to 60 °C working pressure:15bar,Fire rating A & II B, Kitemark certificate No: KM709287,MED certificate No: BSI/MED/3.52/756483
FT03-047G-00	50litre AFFF foam, cartridge operated.Temperature range:5°C to 60°C working pressure:15bar,Fire rating A & II B, Kitemark certificate No: KM709287,MED certificate No: BSI/MED/3.52/756483

Ningbo Kaixuan Fire Control Equipment Co., Ltd

