

CODE: MBK09-120PA-DF

ERP: 0135216

Fire Extinguisher 12Kg Dry Powder Portable

Fire Extinguisher 12Kg with one seam vessel Pressure Gauge Safety Release Valve.

- METALLIC BRACKET INCLUDED

Instructions for use printed on a sticker



CHARACTERISTICS

Approval Type	CNBOP, GTC, ITALY, KKI, MED, MIRTEC, TSE
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Powder
Capacity	12Kg
Extinguishing Agent	ABC 40%
Operating Temperature	-30 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	13Lt L
Cylinder Height	535 ± 5 mm
Cylinder Diameter	190 ± 1.5 mm
Cylinder Neck Thread	M30 ± 1.5mm
Valve Material	HPb59-1 (Nikel Plated)
Cylinder Material	DC01 (St12)
Safety Valve	19-26 bar
Approx. gross Weight	18,14 kg
Approx. Dimensions	700 x 280 mm
Paint Finish	RAL 3000
Packaging Details	1 pc
Discharge time	28 sec



Issue Date: 10/02/2026

Information may change

HEADQUARTERS: KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644

ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com