

CODE: MBK14-500PA-EXT

ERP: 0135323

Trolley Fire Extinguisher 50Kg Dry Powder external cartridge Trolley

50Kg Trolley Fire Extinguisher with 5m Discharge Hose. The external cartridge contains Nitrogen (N₂) as propellant gas.

Soft Material is used in the retaining wreaths of the vessel to avoid injuries and oxidation

> SEPARATE CARRIAGE mounted on the Vessel

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	BSI, MED, MIRTEC, MPA DRESDEN
Extinguisher Type	Trolley
Pressure Type	Cartridge
Suppression Agent Type	Powder
Capacity	50Kg
Extinguishing Agent	ABC 40%
Operating Temperature	-30 to +60 °C
Max Allowable Pressure	20 bar
Test Pressure	30 bar
Volume of Equipment	54 L
Cylinder Height	880±6 mm
Cylinder Diameter	300±1 mm
Cylinder Neck Thread	G2"
Valve Material	HPb59-1
Cylinder Material	HP295
Safety Valve	22-27 bar
Approx. gross Weight	85,3 kg
Approx. Dimensions	1330x550 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



EN1866



Issue Date: 10/02/2026

Information may change

HEADQUARTERS: KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644

ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com